



COLUMNLIFT

VP 451133

Mobile Wheel Engaging Column Lifts up to 7500 kg load capacity per column

DESCRIPTION:

- ◆ Very smooth running due to electro-mechanical drive system
- ◆ High efficiency thanks to smooth-running, low-maintenance ball screw
- ◆ 5-year warrantee for entire spindle drive
- ◆ Excellent lifting column mechanical rigidity guarantees safety and function under any conditions
- ◆ Specially for holding tractors with two crosspieces with adapter kit (can only be used for tractors with corresponding C-rail)
- ◆ Precision-height positioning without overrun thanks to high-quality worm gear motor
- ◆ Lifting carriages with fixed holder
- ◆ Overhead drive unit creates even more space in the work area
- ◆ Workshop-robust and splash-proof control unit
- ◆ Wear-free and easy-to-use membrane keypad

- ◆ Flexible column positioning thanks to excess-length connection cables, guaranteeing suitability across all vehicle categories
- ◆ User convenience with panel operator controls on each individual column
- ◆ High level of flexibility in use due to different operating modes
- ◆ Group and individual column operating modes enable quick and easy replacement of wheel and axle suspensions
- ◆ Microprocessor control and CAN bus-supported monitoring of movement synchronisation and all safety functions
- ◆ Utmost safety thanks to mechanically independent locking device
- ◆ Simple emergency lowering for power failure included as standard

- ◆ System can easily be expanded with up to six columns

- ◆ Streamline COLUMNLIFT design aids manoeuvrability specifically in workstations with restricted space
- ◆ High-quality powder coating available in a variety of colours

STANDARD DELIVERY:

- ◆ 2 individual mobile columns
- ◆ 1 connecting cable (10m) with plug and socket
- ◆ 1 mechanical dolly, repositionable
- ◆ 2 crosspieces with adapter kit

TECHNICAL DATA:

load capacity per column	7500 kg
Motor power per column	1,5 kW
Weight per column	452 kg
Full travel	1750 mm
Raising / lowering time	113 s / 113 s
Power supply	3/N/PE 400 V 50 Hz
Safety class	IP 54

ACCESSORIES:

VZ 971260	Single RGE post (MAHA) 7.5 t lifting capacity
VZ 971182	Remote Control TCNA 10-2 for RGE
VZ 971179	Removable mechanical dolly
VZ 971181	Hydraulic pallet -EXTRA CHARGE PER POST-
VZ 971164	Support stand AB 6-07
VZ 971165	Support stand AB 6-12, mobile
VZ 971166	Support Stand AB 6-20, adj. range 1200-1965mm
VZ 971168	Screw adjust.SP75 f .AB 6-07/12/20
VZ 990456	Linking cable 15 m
VZ 990457	Linking cable 20 m
VV 997486	Packing two posts lifts -Europe-
VV 997487	Packing two post lifts -overseas-