

LIFTING TECHNOLOGY

MOBILE COLUMN LIFT

RGE T
VP 451125



RGE T

VP 451125

The mobile wheel engaging COLUMNLIFT RGE T, with extra wide universal lifting carriage for vehicles with tyre diameters of up to 2.0 m, lifts up to 5.0 t per column. Streamline column design offers a good overview when manoeuvring. The low-maintenance, electro-mechanical drive system ensures extremely smooth running while the excellent mechanical rigidity of the columns guarantees safety and the ability to function in any condition. A high-quality worm gear motor enables precision height positioning without overrun. Column communication is via connecting cable, the power supply via mains power.

PRODUCT DETAILS/ACCESSORIES

- Very smooth running due to electro-mechanical drive system
- High efficiency thanks to smooth-running, low-maintenance ball screw
- 5-year warranty for entire spindle drive
- Excellent lifting column mechanical rigidity guarantees safety and function under any conditions
- Precision-height positioning without overrun thanks to high-quality worm gear motor
- Extra-wide universal lifting carriages specially for vehicles with large tyre diameters up to 2 m
- Overhead drive unit creates even more space in the work area
- Workshop-robust and splash-proof control unit
- Wear-free and easy-to-use membrane keypad
- Flexible column positioning thanks to excess-length connection cables, guaranteeing suitability across all vehicle categories
- User convenience with panel operator controls on each individual column
- High level of flexibility in use due to different operating modes
- Group and individual column operating modes enable quick and easy replacement of wheel and axle suspensions
- Microprocessor control and CAN bus-supported monitoring of movement synchronisation and all safety functions
- Utmost safety thanks to mechanically independent locking device
- Simple emergency lowering for power failure included as standard
- System can easily be expanded with up to six columns
- Streamline COLUMNLIFT design aids manoeuvrability specifically in workstations with restricted space
- High-quality powder coating:
 - Window Grey, RAL 7040 (Columns)
 - Anthracite, Grey RAL 7016 (Lifting carriages)

Scope of delivery:

- 4 individual mobile columns
- 1 supply unit 3 x 400 V / 50 Hz
- 3 connecting cables (10m each) with plug and socket
- 4 hydraulic dollies

TECHNICAL DATA

Load capacity CE per column	5000 kg
Drive power per column	1.5 kW
Weight per column	542 kg
Lifting distance	1750 mm
Raising/lowering time	113 s
Tyre diameter min. - max. 600 - 2000 mm
Supply voltage	3/N/PE 400 V 50 Hz
Protection rating	IP 54

ACCESSORIES

VZ 971334 Single RGE T Post (MAHA), 5000 kg lifting capacity incl. connection cable (->&)- plug

VZ 971182 Remote Control TCNA 10-2 for RGE Up/Down with emergency stop switch

LIFTING TECHNOLOGY

MOBILE COLUMN LIFT

RGE T
VP 451125



VZ 971164	Support stand AB 6-07, load capacity 7500 kg, adjustment range 470-795 mm
VZ 971165	Support stand AB 6-12, load capacity 7500 kg, adjustment range 875-1395 mm, mobile
VZ 971166	Support stand AB 6-20, load capacity 7500 kg, adjustment range 1200-1965 mm, mobile
VZ 971168	Spindle adjustment SP 75 for support stand AB 6-07/12/20
VZ 990456	Linking cable 15 m -Extra charge per cable
VZ 990457	Linking cable 20 m -Extra charge per cable

SUPPLEMENTARY CHARGES

VT 998201	Internal transport -SOUTHMobile column lift 2-4 columns
VT 998202	Internal transport -NORTHMobile column lift 2-4 columns
VT 998205	Internal transport -SOUTHMobile column lift 5-8 columns
VT 998206	Internal transport -NORTHMobile column lift 5-8 columns
VM 996077	Installation costs for mobile column lifts