

# LIFTING TECHNOLOGY

## FOUR POST INGROUND LIFT

VS SQUARE II 6.5 VAN  
VP 252285



### VS SQUARE II 6.5 VAN VP 252285

The four post in-ground lift, with runway, lifts cars and vans of up to 6.5 t. The runway lift, with electro-hydraulic SQUARE lifting unit, is optimally suited for the quick lifting of vehicles. Thanks to the already present rails, an axle jack for wheel-free lifting can also be added to the runway for vehicles with a 3900 mm wheelbase. Optional: Conversion to vehicle reception or wheel alignment lift with 3.5 t wheel-free jack, as well as various types of installation (flush-mounted runway, with or without floor compensation). The torsion-resistant SQUARE posts guarantee maximum safety and outstanding tensile strength, which makes them ideal for wheel alignment.

#### PRODUCT DETAILS/ACCESSORIES

Description:  
Four-post in-floor lift with driving platforms for transporters

##### Description of driving platform:

- Driving platform length 5600mm ideal for cars and transporters
- Ample freedom of movement below the lifting platform thanks to the compact post-lifting unit and resulting optimum lighting below the raised vehicle
- Optional conversion to chassis measurement lift with precisely aligned driving platforms, sliding plates for tension-free wheel support, driving platform levelling and Displacement device with latch rail
- Optionally, can be upgraded to vehicle check-in lift with axle play tester to inspect chassis assemblies
- Optionally prepared for wheel-free jack and level driving platforms with levelling plate sets
- A high-quality powder-coated platform covering assists in corrosion protection and adds a significant upgrade in terms of appearance
- Optional driving platform coating with granulate coating
- Additional corrosion-resistant treatment in the seam region and body cavity-sealing increases the service life
- Pre-integrated compressed air connection and optional 230V/1PH energy supply in runways
- All cables are protected inside the SQUARE post
- Optional, no-dazzle rotatable LED lighting
- Various assembly variants for optimum use:
  - Driving platform resting on floor with low drive-on height and platform movement area with no tripping hazard edges
  - Driving platforms flush with floor to facilitate driving onto the lift, no protruding assemblies in the lift area
  - Driving platforms flush with floor to facilitate driving onto the lift, no protruding assemblies in the lift area with complete floor levelling of the platform movement area with no tripping hazard edges
- Runways and ground levelling pre-equipped for the use of an optional axle lift

- Pinch point and shear point protection thanks to CE stop

##### SQUARE lift unit:

- Outstanding rigidity and optimum safety thanks to torsion-resistant square post
- Very quiet pump and very quiet electric motor in corrosion-proof oil-submerged design, optionally with bio oil
- Electronic lift control with no-contact, wear-free limit switches and visual error display
- Very smooth running due to special long-life nickel coating on posts that promotes sliding, with robust, low-maintenance post design
- Protected internal hydraulic safety cylinder guarantee lengthy service life
- Mobile synchronisation and safety yoke for careful distribution of force in the post guide as standard
- High lifting/lowering speeds are guaranteed (max. 38/38 s)
- Lift system with synchronisation for electronic synchronism of the front and rear piston couple guarantees optimum precision of the front and rear piston couple
- Battery-operated emergency lowering
- Optimisation of workplace ergonomics mentioned thanks to optional, standard-independent control via traffic-light energy module or flush-mounted switching system

##### Scope of delivery:

- Driving platform 5600 mm powder-coated anthracite (RAL 7016)
  - Lift unit with hydraulic assembly
  - Ramps and drive-on plates
  - Rapid-action compressed-air coupling mounted on driving platform
  - Wiring and mounting material
  - Installation box/installation frame not included in delivery
  - Emergency DOWN cable for connection to switch box
  - Control unit with 4 x 10 m control cables (flexible oil cables)
  - Lockable master switch
  - Operating manual and test log
  - EC Declaration of Conformity CE



# LIFTING TECHNOLOGY

## FOUR POST INGROUND LIFT

**VS SQUARE II 6.5 VAN**  
VP 252285



VM 996190	Montagekosten Sechsstempel-Fahrflächen-Hebebühne inklusive Nivellierung	VT 998240	Internal transport -NORTHtwo-/Four-post lift with runways
VM 996214	Montagekosten Fundamentrahmen für bodenebene Fahrflächen brücke (Vierstempel)	VT 998237	Internal transport -SOUTHInstallation tub (1 - 4 pcs)
VM 996020	Montagekosten Bodenausgleich bei Einbau in Zwei-/Vier Stempel-Fahrflächen-Hebebühne	VT 998238	Internal transport -NORTHInstallation tub (1 - 4 pcs)
VM 999035	Hydraulic Oil (HLP-D 22) per Litre -NET PRICE	VT 998241	Internal transport -SOUTHFoundation frame for runway
VM 999036	Environmental-Friendly Hydr. Oil (PE-B 30), per litre -NET-	VT 998242	Internal transport -NORTHFoundation frame for runway
VT 998239	Internal transport -SOUTHtwo-/Four-post lift with runways	VV 997572	Packing Charges Four Post Inground Lift, Runway Type -within Europe-