

VEHICLE TESTING TECHNOLOGY AXLE DAMPING TESTER

C_MSD C 2.5 W250
VP 215049



C_MSD C 2.5 W250
VP 215049

The axle damping test bench C_MSD is characterised by a fast and precise mechanical testing of the axle damping. Through the frequency-controlled plate activation via electric motors, the maximum vibration amplitude is calculated and then the axle damping is evaluated according to the Lehr damping principle. The fully automatic test sequence, including the calculation of axle and vehicle weight, saves time and allows a reliable assessment of the axle damping.

PRODUCT DETAILS/ACCESSORIES

Description:
Shock absorber tester for quick and precise, physical shock absorption testing of cars and vans up to 2.5 t axle load (traversable) with a track width of 2,500 mm

Specially suitable for car reception, diagnostic and PTI test lanes
For wider vehicles such as SUVs, off-roaders or vans

- Evaluation based on Lehr's damping ratio
- Automatic measurement of axle and vehicle weight with transfer of weight to brake tester (optional)
- Fully-automatic test sequence launched once plate load is more than 60 kg on both sides
- Frequency-controlled plate excitation by electric motors to determine the maximum vibration amplitude, with subsequent evaluation of axle damping
- Noise search function for pinpointing interference noises in the vehicle directly on the test stand (optional, only in conjunction with EUROSYSYSTEM)
- Floor unit as self-supporting framework
- Parallelogram-guided test plates and therefore no fixed wheel

testing point necessary

In conjunction with CONNECT Web client:

Display on terminal device (Smart device, PC,)

- with evaluation by Lehr's damping ratio D with deviation display and graphics
- In conjunction with EUROSYSYSTEM: Display on PC screen with evaluation by Lehr's damping ratio D with deviation display and graphics

Design:

- Shock absorber tester S W250
- Self-supporting, enclosed floor assembly (Compact)
- High-quality powder coating: anthracite grey, RAL 7016

Scope of delivery:

- Shock absorber tester C_MSD C 2.5 W250 Enclosed floor assembly
- Prepared for connection to CONNECT test lane

Attention:

In combination with brake tester, please note installation length 2.95 m (C_MBT W250 = 2.67 m / C_MBT W280 = 2.95 m)

TECHNICAL DATA

Axle load (test capacity)	2200 kg
Axle load (support capacity)	2500 kg
Min. track	880 mm
Max. track	2500 mm
Drive power	2 × 1.1 kW
Excitation lift	6.5 mm
Excitation frequency (regulated)	2 - 10 Hz
Maximum plate lift	70 mm
Measurement display (damping ratio D)	0.02 - 0.3 (without units)

VEHICLE TESTING TECHNOLOGY AXLE DAMPING TESTER

C_MSD C 2.5 W250
VP 215049



TECHNICAL DATA

gG fuse	16 A
Power supply	1/N/PE 230 V 50/60 Hz
Floor unit dimensions (H x W x L)	280 x 800 x 2924 mm

ACCESSORIES

VZ 975633 Calibration-Device MSD 3000

SUPPLEMENTARY CHARGES

VT 998281 Transport Werkverkehr -SÜDMBT W250/RS4/
W280/RS5, C13.0 MSD-Plus -ungeteilt/Compact-

VT 998282 Transport Werkverkehr -NORDMBT W250/RS4/
W280/RS5, C13.0 MSD-Plus -ungeteilt/Compact-

VM 996142 Montagekosten MSD inkl. Einweisung und
Kalibrierung