



POWERDYNO

VP 230035

Single Roller Dynamometer

DESCRIPTION:

- ◆ Single-axle single roller dynamometer for cars with axle load of up to 2400 kg, eddy-current brake included, ideally suited for performance measurements, tuning and diagnostic work in powerful vehicles
- ◆ Test speeds of up to 300 km/h
- ◆ Tyre rolling action as it would be on the road
- ◆ Tyres are preserved as a result of limited flexing action
- ◆ Simple restraining mechanism for quick vehicle fixation

High level of flexibility in use due to extensive variety of operating modes, covering all fields of application:

- ◆ Static power measurement at constant RPM
- ◆ Static power measurement at constant speed
- ◆ Static power measurement at constant tractive force
- ◆ Dynamic power measurement with adjustable acceleration
- ◆ MAHA towing power measurement guarantees the highest degree of accuracy when measuring power:
Precision calculation of the parasitic losses of the dynamometer, of the vehicle's drive train and the tyre to roller friction and flex losses
- ◆ Tachometer testing with up to ten freely selectable test points
- ◆ Distance measurement included
- ◆ Stopwatch function for measurement of acceleration between optional speed markers as standard
- ◆ Optional load simulation with freely programmable load profile
- ◆ Optional driving simulation with freely programmable speed profile
- ◆ Option of storing programmed profiles in database

Professional, intuitive-use software for the highest expert standards with:

- ◆ continuous graphic display and recording of up to 16 freely selectable parameters per performance measurement cycle on one measurement screen.

- ◆ In addition to the current performance measurement cycle, fade-in of up to three stored cycles on the measurement screen for optimum comparability during calibration work
- ◆ Two circular dial displays for RPM and speed as well as current oil temperature display, ensuring constant control of key parameters during performance measurement
- ◆ Determination of wheel power, power dissipation, engine power and torque
- ◆ Standardised extrapolation of motor power in line with DIN 70020, EEC 80/1269, ISO 1585, JIS D 1001 and SAE J 1349 (configuration-dependent)
- ◆ Circular dial display of motor power, RPM, speed and tractive force during simulation cycles
- ◆ Colour-highlighted user prompts integrated within the circular dial facilitate the accurate reproduction of simulation cycles
- ◆ With radio remote control as standard for complete control of the dynamometer from within the vehicle.
- ◆ Radio remote control with long-life battery and charging station
- ◆ Cooling fan switched on and off either at the control console or with the radio remote control
- ◆ With interface box including stand and long connection cable as standard for optimum placement at the dynamometer with MAHA plug-in CAN-DRZ module card for connecting RPM sensor.
- ◆ Interface box optionally upgradeable with MAHA plug-in card for comprehensive recording of external Ambient data such as air temperature, air pressure, rel. humidity and intake temperature
- ◆ Interface box optionally upgradeable with MAHA plug-in analogue input module card with 4 sensor inputs for temperature and pressure sensors or lambda sensors.

DESCRIPTION:

- ◆ Optional connection of MAHA MGT 5, MDO 2 LON and MET SERIES emission testers
- ◆ Optional connection of Krupp/AIC fuel consumption measuring instruments for petrol- and diesel engines

MCD 2000 Communication Desk

- ◆ Robust and multifunctional metal encasement
- ◆ Integrated switch cabinet for housing electronic components
- ◆ Lockable drawer for keypad and PC mouse and storage compartment for small items of equipment
- ◆ VESA standard bracket for holding the all-in-one PC or PC monitor
- ◆ Can be extended with optional PC storage compartment or side shelves
- ◆ Varnished with high-quality powder coating:
 - window grey, RAL 7040 (switch cabinet)
 - anthracite grey, RAL 7016, (side faces)

STANDARD DELIVERY:

MCD 2000

- ◆ MCD 2000 Communication Desk
- ◆ interface box 1 including stand and connection cable with plug-in environment module (CAN-PTH module) card for recording air temperature, air pressure, humidity with plug-in RPM module (CAN-DRZ module) card for RPM recording via trigger clamp, light signal sensor, piezo clamp, clamp W and TDC sensor (insertion of max. 4 modules per box possible)
- ◆ Radio remote control for dynamometer operation with battery and charging station
- ◆ Cooling fan control
- ◆ Measuring program

Roller Set

- ◆ Robust self-supporting, closed roller set with an eddy-current brake
- ◆ Varnished with high-quality powder coating, gentian blue RAL 5010

TECHNICAL DATA:

Axle load	2500 kg
Compressed air max.	7 bar
Track width	700 mm - 2200 mm
Roller set rotating mass	280 kg
Roller diameter	504 mm
Roller camber	5 mm
Test speed max.	300 km/h
Wheel power (static) max.	260 kW
Wheel power (dynamic) peak >	1000 kW
Electric motor with a drive power rating (optional)	22 kW
Tractive force max.	7000 N
Measurement accuracy wheel power measurement (from measured value) +/-	2 %
Fuse gG	63 A
Power supply	3/N/PE 400 V 50 Hz
Dimensions communication desk (H x W x D)	1500 mm x 860 mm x 420 mm
Converter cabinet dimensions (H x W x D)	1000 mm x 800 mm x 400 mm
Dimensions roller set (L x W x H)	1095 mm x 3324 mm x 512 mm
Weight roller set	1300 kg
Communication desk weight incl. packaging	150 kg

ACCESSORIES:

VZ 910176	Industrial PC All-in-One
VZ 910177	Industrial PC Compact
VZ 955275	PC-Holder for placement inside MCD 2000
VZ 910052	PC-Keyboard and Mouse
VZ 910091	DIN A4 Ink Jet Colour Printer
VZ 910165	PC Flat Screen 22 inch (TFT Standard)
VZ 910192	Simultaneous Display Unit 40"
VZ 955244	Rotatable & Folding Wall Holder for TFT
VZ 910179	HDMI Cable 15 m
VZ 910180	HDMI Cable
VZ 910181	HDMI-Splitter 4-Port
VZ 955274	Side Shelf for MCD 2000
VZ 955277	External PC Storage Shelf for MCD 2000
VZ 990275	Interface Box 2
VZ 911145	Pressure temp. module (CAN P2T2 Module)
VZ 911146	OBD Module (CAN OBD Module)
VZ 911240	Analogue Input Module (CAN-AIN4 Module)
VZ 990438	Analog Outputs LPS 3000/MSR
VZ 990221	RPM Light Signal Sensor w. reflective spots
VZ 990211	Trigger Clamp for MGT 5
VZ 990225	Oil temperature sensor for cars
VZ 990276	Exhaust Temperature Sensor TEMP
VZ 911150	Software Module Emission 1 driving cycle,
VZ 911151	Software Module Emission 2 lug-down
VZ 990278	Board (DT Module)
VP 994013	AIC-1204 HR 2000
VZ 975498	Conn. kit for petrol cars, pressure control valve
VZ 975499	Connecting Kit for Diesel Powered Cars, Adapter
VZ 994014	Carrying Case for AIC-1204 and Accessories
VZ 990427	Wideband Lambda/AFR kit
VZ 911152	Connection Package Petrol Emissions
VZ 911153	Conn. pack. diesel emiss. f. conn. of
VZ 911154	Conn. pack. diesel emiss. hand terminal MDO 2
VZ 911155	Conn. pack. ext. measurm. station emissions
VZ 935266	Set of Anchor Rails for MSR
VZ 935268	Set of Ground Sleeves 140 mm for MSR
VZ 935267	Set of Ground Sleeves 190 mm for MSR
VZ 935191	Vehicle Restraint System rear side
VZ 935230	Attachment Points for Anchor Rails (4 pieces)
VZ 935215	Ni/Cr Coating for Running Rollers
VZ 935219	Preparation for Additional Eddy Current Brake
VZ 935216	Add. Eddy current brake for MSR
VZ 950062	Converter Cabinet for Control of Drive Motors
VZ 975652	Calibration Device LPS R50 universal
VW 997563	Packing MSR 500/800/830/850 -Europe-
VW 997564	Packing MSR 500/800/830/850 -overseas-

