

# SPECIFICATION

## ATL



### FOUR-POST LIFT ATL-VERSION

#### MODEL: CARLIFT II 3.5 ATL Class IV

Art.-No.	Qty	Description	Specifications-No.
----------	-----	-------------	--------------------

VP 251101

### 1 Four-Post Lift with 3,5 t Lifting Capacity

#### MODEL: CARLIFT II 3.5 ATL Class IV

##### **Specifications:**

- \* Column construction free of base framework
- \* Four-Post Lift with hydraulic drive
- \* Electro-static powder paint:  
dark grey RAL 7016/blue RAL 5010

##### **Special Features:**

- Preparation Runways for Installation of Play Detector,  
MODEL: PMS 3/P –pneumatic-  
only 1 Test Plate (on right platform) incl. Preparation Electrics  
and cover for Runway Recess
- Driving platform recess for Turning plates  
Length 390 mm, Height 50 mm
- Control unit mounted on frontside, right of the column

##### **Technical Data:**

- Driving platform dimensions (special version).....4400x630 mm
- Height of driving platform (special version).....170 mm
- Clearance between driving platforms.....880 mm
- Driving platform recess for mech. Turning plates....390x50 mm

##### **ATTENTION:**

*Above ground or inground set needed (see options) !  
Please indicate when ordering!*

##### **Options**

VP 985050

1 Axle Play Detector MODEL: PMS 3/P –pneumatic-  
only 1 test plate (on right platform) –Retro-fitting set-

VZ 985050

1 Axle Play Detector MODEL: PMS 3/P –pneumatic-  
only 1 test plate (on right platform) –Installation ex works-

VZ 995692

1 Installation costs for Axle Play Detector –pneumatic- only 1 test  
plate at installation ex works –NET-

# SPECIFICATION

## ATL



### FOUR-POST LIFT ATL-VERSION

#### MODEL: CARLIFT II 3.5 ATL Class IV

Art.-No.	Qty	Description	Specifications-No.
----------	-----	-------------	--------------------

#### Options

VZ 971307	1	Above ground set, consisting of long ramps (2) and roll over bar (2)	
VZ 971308	1	Above ground set (drive over capable), consisting of long ramps (4)	
VZ 971309	1	Inground set, consisting of short flaps (2) and roll over bar (2)	
VZ 971302	1	Inground set (drive over capable) consisting of short flaps (4)	
VZ 971333	1	Integrated Lighting inside of runways (4 Fluorescent Tubes)	
VZ 971148	1	Integrated Lighting (4 Fluorescent Tubes) for Carlift	
VZ 990029	1	Light Barrier Safety Device to avoid contact with ceiling	
VZ 971146	1	Extra Charge for Granulate Coating of Driving Platforms (Carlift)	
VP 985044	1	Axle Jack, Hydro-Pneumatic Scissors Lift with 2.0 t load capacity MODEL: AL II 2.0 PH	
VZ 975181	1	Air Pressure Servicing Unit with Fastening Iron (0 - 10 bar)	
VZ 990345	1	Wireless Radio Handlamp MODEL: RHL –Extra Charge-	

#### Change:

- Special features:  
Preparation Runway for Installation PMS (previously PMS in Standard Delivery) (08.10.07)
- Height of driving platform 170 mm (previously 190 mm) (26.10.07)
- Option: PMS 3/P –Installation ex works- (VZ 985050) (14.12.07)
- Option deleted: PMS 3/P –Retro-fitting Set- (VP 985050) (24.09.13)
- Option Integrated Lighting (VZ 971333) (13.08.15)