

SPECIFICATION

ATL



**TWO-CYLINDER LIFT
WITH DRIVING PLATFORM
FOR CARS/VANS UP TO 3.5 t LIFTING CAPACITY
MODEL: ZS-SQUARE II – ATL Class IV**

Art.-No.	Qty.	Description	Specifications-No.
----------	------	-------------	--------------------

VP 252277

**1 Two-Cylinder Lift with Driving Platform
with 3.5 t Lifting Capacity, flush-mounted
without Floor Levelling Platform**

MODEL: ZS SQUARE II – ATL Class IV

Special Features:

- *Two-Cylinder Lift with Runways (VP 252196)
MODEL: ZS SQUARE II 3.5 P*
- *Driving platform length 4400 mm
Driving platform width 617 mm
Driving platform cut-out for turning plates 390 x 50 mm
(Attention: Special foundation plan for flush-mounted
installation!)*
- *Flush-fitted Runway Installation (VZ 972425)*
- *Play Detector, MODEL: PMS 3/XL (VP 985024)
incl. wireless Radio Handlamp Model: RHL
with lowerable prism blocks for installation on front of Scissors
Lift, operated by the lift's hydraulic control unit*
- *Installation Costs for Standard Installation of
Play Detector (VZ 995021)*
- *Powder paint coating RAL 7016*

Possible Options for ATL Version:

VP 985043	1	Axle Jack, Hydro-Pneumatic Scissors Lift with 2.0 t Lifting Capacity Model: AL II 2.0
VZ 972153	1	Auto chocks (2 pcs.) only f. flush-fitted inst. of runways (instead of Drive-over Flaps) 4 pcs. necessary for Lift
VZ 975181	1	Air Pressure Servicing Unit with Fastening Iron
VZ 972433	1	LED Illuminant, 4 pcs
VZ 975013	1	Runways with Granulate Coating
VZ 972555	1	Installation tub for lifts 1350 mm cylinder distance MODEL: EW SA 1350

SPECIFICATION

ATL



**TWO-CYLINDER LIFT
WITH DRIVING PLATFORM
FOR CARS/VANS UP TO 3.5 t LIFTING CAPACITY
MODEL: ZS-SQUARE II – ATL Class IV**

Art.-No.	Qty.	Description	Specifications-No.
----------	------	-------------	--------------------

Changes:

-Special Features: Powder Coating RAL 7016 (25.01.21)

For transport, packing and assembly charges please refer to current price list!