

BRAKE TESTING TECHNOLOGY

MBT 4000 SERIES

MBT 4200 LON W COMPETENCE VP 410154





MBT 4200 LON W COMPETENCE VP 410154

The test-lane-compatible roller brake tester MBT 4200 LON W COMPETENCE is designed for the brake testing of trucks with axle loads of up to 13.0 t. Its standard split design for pit installation ensures a high level of flexibility within the working area. Its multi-analogue display, with four pointer gauges, enables the display of brake, side-slip and shock absorption test results (0-8 kN and 0-40 kN).

PRODUCT DETAILS/ACCESSORIES

Description of the MBT 4200 LON:

Test lane-enabled roller brake tester with multi-analogue display for lorries with an axle load of up to 13 t

- Divided design supplied as standard for installation in a working pit enables a high level of flexibility with regard to the area of use
- The dimensions offer the best testing opportunities for standard cars and lorries
- Multi-analogue display with four pointer indicators

(Diameter: 4 x 350 mm)

- Measured value display
- 0 8 kN / 0 40 kN
- Display option for:
 - Brake tester
 - Wheel arch tester
 - Shock absorption tester
- Difference display (three-digit + LED bar) for displaying:
 - Difference in braking force in %
 - Difference in shock absorption in %
 - Deviation in wheel arch in m/km
 - Results evaluation using additional coloured LED bars
 - · User guidance using alphanumerical display
- Program control using 32-bit microprocessor electronics

enables the finest resolution for the measurement results Dimensions of display (H \times W \times D) 1060 \times 870 \times 300 mm

- Comprehensive package of functions for professional testing, such as:
 - · Delayed automatic switch-on after entering the tester
 - Automatic start-up monitoring supplied as standard to avoid tyre damage
 - Automatic slip cut-off with pointer stop and automatic restart already included as standard
 - Automatic exiting aid supplied as standard to enable the

- driven axles to conveniently exit the tester
- · Automatic cut-off after exiting the tester
- Single-wheel switching for differentiated consideration of each wheel
- · Robust and long-lasting design due to:
 - Electronic, temperature-compensated strain gauge system for highly precise measurement results under all environmental conditions
 - Roller surface welded
 - · Optional, free plastic coating on the test rollers
 - 32-bit microprocessor electronics for process control and monitoring of all the safety functions
 - Lockable main switch
 - RS 232 interface connection
 - Splash-proof motors work reliably, even under high-stress environmental influences
 - Weighted test rollers with groove ball bearings ensure maximum precision and complete driving comfort and guarantee a long service life for the entire tester
 - Internationally recognised TÜV certificate as per issue 9/2011 of the Verkehrsblatt [German Transport Gazette]
 - Star-delta circuit to avoid high inrush currents
 - RS 2 roller set design with space-saving motor integration underneath the test rollers
 - Rear roller elevated by 40 mm guarantees highly precise measurement results, particularly for trailer axles.
 - Self-supporting divided roller set
 - Varnished with high-quality powder coating: Anthracite Grey, RAL 7016

Scope of delivery:

- Analogue display with four pointer indicators and an integrated switch cabinet
- MBT 4000 RS 2 roller set with preparation for weighing equipment
- Two VARIODATA digital displays
- · RECO 1 remote control

TECHNICAL DATA

Axle load (can be driven over) 13000 kg

Drive power 2 x 9 kW



BRAKE TESTING TECHNOLOGY

VP 410154

MBT 4200 LON W COMPETENCE




MBT 4000 SERIES

TECHNICAL DATA

| Test speed | 2.3 km/h |
|----------------------|--------------------|
| Roller length | 1000 mm |
| Roller diameter | 202 mm |
| Roller axle distance | 430 mm |
| gG fuse | 50 A |
| Power supply | 3/N/PE 400 V 50 Hz |

| ACCESSORIES | | | | | |
|-------------|--|---|--|--|--|
| VZ 955278 | Add-on Kit Brake Tester Directive Model: Directive 2011 | VZ 935169 | Mechanical-Hydraulic Roller Set Lift for MBT 4000/7000 RS.No.2/W | | |
| VZ 930027 | Additional Charge for Reinforced Roller Set max. Axle Load 15 t | VZ 935170 | Angle Iron Frame for Lifting of Roller Set, with working pit | | |
| VZ 930047 | Additional Charge for 2 Re-inforced 11kW drive motors Fused 63 Amp slow. | VZ 935172 | Angle Iron Frame for Lifting of Roller Set (for Balzer Pit) | | |
| VZ 935010 | Flush-Floor Roller Set (both Front & Rear Rollers raised 40 mm) for MBT 4000 RS.No.2 | VZ 935238 | Roller Set Lift, Mech./Hydr. MBT 4000/7000 RS.No.2/W with Angle Iron Frame (1-Piece) | | |
| VZ 935142 | Approach Ramp MBT 4000 RS No.2 (2 pcs.), made of Steel | VP 935236 | Floor Anchors -Above-Groundfor Raisable Roller Set | | |
| VZ 935275 | Vehicle Weight-Bearing Roller Cover Plates (4 | VP 935237 | Floor Anchors -In-Groundfor Raisable Roller Set | | |
| VZ 935073 | pcs.), Galv. Steel, for MBT 4000 RS No. 2 Angle Iron Frame for MBT 4000 RS.No.2 for | VZ 935232 | Adapter Set Continental CTC II / Workshop Tab -NET- | | |
| VZ 300070 | Weighing Machine with pit | VZ 935276 | Prefitting with holder set for Continental CTC II | | |
| VZ 935157 | Angle Iron Frame for MBT 4000 RS.No.2 for Weighing Machine with Pit, galvanized | VZ 935110 | -NET PRICE- | | |
| VZ 935074 | Angle Iron Frame for MBT 4000 RS.No.2 for | | Production - Welded) | | |
| /7 005155 | Weighing Machine w/o Pit | | ING SYSTEM AND SPECIAL VOLTAGE | | |
| VZ 935155 | Weighing Machine w/o Pit, galvanized | VZ 935072 | Driving and Testing direction manually switchable at console | | |
| VZ 935180 | Center Cover between Roller Sets, for MBT 4000 | VZ 935134 | Driving in both directions | | |
| /Z 975547 | Weighing device STATIC for MBT 4000/6000/7000 | VZ 990181 | 4 wheel drive regulator set for Visco and Rigid 4 WD (MBT 4000/7000 Series) | | |
| /Z 975548 | Weighing device STATIC/ DYNAMIC for MBT 4000/6000/7000 | | DC-Brake for MBT 4000/7000Roller Sets | | |
| /Z 935077 | Two Testing Speeds | | Special voltage 3 x 230 V 50Hz | | |
| | Roller Heating | ACCESSORIES ANALOG-/SIMULTAN- EOUS DISPLAYS | | | |
| VZ 985061 | Hydr. Load Simulator Single HD Cylinder Model: MLS 1100 | VZ 955257 | Foot for display cabinet for free-standing installation | | |
| /Z 985052 | Hydr. Load Simulator Double HD Cylinder Model: MLS 2100 | VZ 955256 | swivable | | |
| VZ 985018 | Hydr. Load Simulator Double HD Cylinder Model: MLS 2150 | VZ 950057 | Simultanous Display for MBT 4000/7000 LON/- EUROSYSTEM TYP: MSA T CLASSIC | | |
| VZ 985053 | Hydr. Load Simulator Double HD Cylinder Model: MLS 2200 | VZ 950058 | Simultanous Display for MBT 4000/7000 LON/- EUROSYSTEM TYP: MSA T VARIODATA | | |
| /Z 985054 | Hydr. Load Simulator Double HD Cylinder Model: MLS 2300 | VZ 950059 | Simultanous Display for MBT 4000/7000 LON/- EUROSYSTEM TYP: MSA T COMPETENCE | | |
| /Z 935251 | MLS Weight Simulator Operation via Radio | VZ 955252 | Differential display for Simultanous Display MSA | | |
| | Remote Control MRC 1100 (not for MLS 2300) | VZ 955253 | 1 3 | | |
| /Z 990201 | Converter Board for Control of Hydraulic Load Simulator Roller Set Lifting | VZ 955254 | LED-running letters (16 digits) with convenient operator guidance | | |
| /Z 935194 | Floor Rails 4 m (2 pcs) for Hydr. Load Simulator (VZ 985053 or VZ 985054) | VZ 955269 | Installation Kit to attach Simultanous Display MSA to Wall (approx. 90° swivalable) | | |
| /Z 935195 | Floor Rails 4 m (2 pcs) for Hydr. Load Simulator (VZ 985053 or VZ 985054) | VZ 955255 | 180° swivalable) | | |
| /Z 935198 | Lashing Straps for Hydr. Load Simulator (2 pcs) | VZ 955270 | Foot for Simultanous Display MSA, (approx. 180° swivalable) for free-standing installation | | |
| /Z 935199 | Fastening Set for Hydr. Load Simulator | VZ 955271 | Support for Simultaneous Display MSA CLASSIC, | | |
| /Z 935200 | Fastening Clamps (2 pcs.) for Hydr. Load Simulator | | for Inst. to Communication Desk MCD | | |
| /Z 935264 | Mechanical-Hydraulic Lifting of MBT 4000/7000 | VZ 950064 | 1 3 | | |
| | RS.No.2 | | IES PRINTER AND REMOTE CONTROLS | | |
| VZ 935112 | Adapter frame to convert MBT 7000 foundation frame to MBT 4000 roller set | | Infrared Remote Control IFB3 | | |
| | Harrie to MIDT 4000 Toller Set | VZ 990050 | Pedal force meter | | |





BRAKE TESTING TECHNOLOGY

MBT 4000 SERIES

MBT 4200 LON W COMPETENCE VP 410154



| VP 990434 | Pedalforce Meter MODEL: PFM 1000 | VZ 910192 | LCD simultaneous display unit 40 incl. pedestal; |
|-----------------|---|------------------------|---|
| ACCESSORI | ES SAFETY SYSTEMS | | HDMI -NET PRICE- |
| VZ 955088 | Key Switch for Emergency Stop | VZ 955244 | Rotatable & Folding Wall Holder f. TFT Industrial- |
| VZ 955045 | Emergency Switch | VZ 910193 | or TV Flat Screens (up to 42) HDMI Cable 5 m -NET PRICE |
| VZ 955014 | Working hour meter | VZ 910193 VZ 910179 | HDMI Cable 15 m -NET PRICE |
| WEATHER P | ROTECTIVE ACCESSORIES | VZ 910179 VZ 910180 | HDMI Cable 30 m -NET PRICE |
| VZ 955080 | Thermostat-Controlled Heater for Electro-Cabinet | VZ 910180 | HDMI Splitter, 4-port incl. 2 m cable -NET PRICE |
| ACCESSORI | ES PRESSURE EQUIPMENT AND RADIO EQUIPMENT | VZ 910091 | A4 Ink jet colour printer (incl. printer cable) -NET |
| VZ 980034 | Pneumatic pressure converter integrated into roller set measurement range 0 - 20 bar | | PRICE- |
| VZ 980035 | Start set radio controlled pressure converter | VZ 955295 | Radio Touchscreen MODEL: FTS 2018 -NET- |
| VZ 910154 | Radio remote control Model: FFB3 incl. reception | VZ 955296 | Docking station as charger incl. power supply unit FTS 2018 / C_Tablet-PC -NET- |
| | module | VZ 955237 | AP Transmitter/Receiver Unit (Indoor Access |
| VZ 910157 | Radio remote control FFB3 (-EXTRA CHARGE to | | Point) |
| VZ 910156 | RECO 1-) Radio remote control/Radio Hand-held terminal | SUPPLEMEN | NTARY CHARGES |
| | FFB3-FHT (-EXTRA CHARGE to FFB3-) | VT 995707 | Transportkosten Bremsprüfstand MBT 4000/5000/7000-Serie |
| VZ 980029 | Pneum. Radio-Controlled Pressure Converters, Meas. Range 0 - 20 bar, MODEL: RCD 40 | VT 995655 | Transportkosten PC-Recheneinheit in Verbindung mit Pult |
| VZ 985028 | Hydr.Radio-Controlled Pressure Converters, Range: 0 - 160 bar MODEL: RCD 30 - 160 bar | VT 995068 | Transportkosten Schaltschrank, Simultananzeige, PC-Pult pro Stück |
| VZ 955071 | Flashing Light with Periodical Signal Horn for | VT 995004 | Transportkosten Einbaurahmen geteilt |
| V7.00000 | Radio Controlled Pressure Converters | VT 998147 | Transportkosten Einbaurahmen ungeteilt |
| VZ 990090 | Warning Lamp f. Radio-Control. Pressure Converters when being removed from Re- Charging Box | VT 995069 | Transportkosten hydraulischer Gewichtssimulator |
| ACCESSORI | ES HARD- AND SOFTWARE | VT 995711 | Transportkosten Einbaurahmen für |
| | Software LON Basic for external PC | | Rollensatzanhebung |
| VZ 911265 | Software module LON Basic Plus with SP- | | Hydraulic Oil (HLPD 32) per Litre -NET PRICE |
| | Program Basicof Software BASIC-LON | VM 996113 | Assembly costs Brake Tester MBT 4250/-7250 LON MBT 5200/-6200 |
| VZ 911273 | Software module LON Basic HR with projection program | VM 995148 | Routine Test/Calibration acc. to Verkehrsblatt 24/2020 Truck Brake Tester |
| VZ 910140 | USB/RS 232 Converter for Connection to PC/ Laptop w/o. RS 232 Interface -NET- | VM 996088 | Montagekosten Allradregelsatz bei Neuinstallation |
| VP 186050 | Communication Desk EUROSYSTEM Car/Truck (w/o electronics) Model: MCD 2000 | VM 996090 | Assembly Costs Radio Pressure Converters (max. 10 pcs.) per unit/recharging box |
| VZ 955273 | Printer Compartment for Communication Desk EUROSYSTEM MCD 2000 | VM 996177 | Montagekosten Funk-Touchscreen FTS -bei Neuinstallation |
| VZ 955274 | Side Shelf for Comm. Desk EUROSYSTEM MCD 2000 | | Assembly Costs per Display Unit |
| VZ 955277 | External PC Storage Shelf for Communication Desk EUROSYSTEM MCD 2000 | | Montagekosten Niederzieh- und Hebevorrichtung -nach Aufwand- |
| VZ 910177 | Industrial PC Compact with Windows 10 -NET PRICE | VM 996185 | Montagekosten Bodenanker für Rollensatzanhebung -nach Aufwand- |
| VZ 955275 | Holder for Compact/Performance PC, suitable for placement inside MCD 2000 desk | VM 996114 | Pre-assembly Brake Tester MBT 4000/5000/6000/7000 with 20m cable |
| VZ 910052 | PC Keyboard and Mouse -NET PRICE | VM 996115 | Connection and Calibration MBT |
| VZ 910002 | PC Flat screen 24 VGA/DVI/HDMI, (TFT standard) | \/\/007504 | 4000/5000/6000/7000 with 20 m cable |
| . 2 3 . 0 2 0 0 | -NET PRICE- | VV 997584 | Packing Charges Roller Set Lift |



