

LIFTING TECHNOLOGY TWIN SCISSORS LIFT

TWIN F IV 3.5 U
VP 250218



TWIN F IV 3.5 U VP 250218

The twin scissors lift TWIN F IV 3.5 U, for flush-floor installation, lifts vehicles of up to 3.5 t. Thanks to its innovative cylinder lift-out support, it reaches its full lifting power at even the lowest lifting height. Low-noise raising and lowering with speed delay is also possible in the lowest position. The continuously adjustable support plate length ensures comfortable operation, subsequent pushing of the vehicle is not required.

ACCESSORIES

VZ 970045	Ductile Plastic Blocks (4 pcs.) 95 x 132 x 340 mm
VZ 975074	Hard Rubber Blocks, Plug-in Type (4 pcs.) 120 x 100 x 50 mm
VZ 975069	Plastic Chocks (4 pcs.) (47 x 132 x 340 mm)
VZ 970052	Extension of Hydraulic Hoses per Metre for Twin Scissor Lift
VZ 971104	Light Barrier Safety Device to avoid Contact with Ceiling

VZ 990462	Mains power supply 3x380-400V+PE; 60Hz -Extra Charge-
-----------	---

SUPPLEMENTARY CHARGES

VT 998064	Transportkosten Doppel-Scherenhebebühne
VM 996069	Installation Charges Twin Scissors Lift
VM 996072	Install. Charges f. Ceiling Light Barrier -T&M Basis
VM 999021	Installation Material (16 x Anchor bolts M 10 x 130)
VM 999035	Hydraulic Oil (HLP-D 22) per Litre -NET PRICE