

LIFTING TECHNOLOGY

TWO POST INGROUND LIFT

ZS DUETT 3.5 FT
VP 252319



ZS DUETT 3.5 FT VP 252319

Two-post inground lift with flat head supports, to pick up vehicles in the sill area. Suitable for cars, pick-up points underneath the vehicle.

PRODUCT DETAILS/ACCESSORIES

Description:

Two-post inground lift with flat head supports, to pick up vehicles in the sill area. Suitable for cars, pick-up points underneath the vehicle

Flat head support (FT H):

- Flat head extensions adaptable for different vehicle types, telescopic from 1400 - 2000 mm in standard
- Flexible, optional range of support plates in 'longer - wider - flatter' versions ensures perfect accommodation of all current and future vehicle models
- Large pick-up areas due to exchangeable support plate system cover the entire vehicle spectrum
- Easier, tyre-preserving drive-on thanks to all-round bevelled extensions combined with low construction height and rubber support plate (height no more than approx. 60 mm)
- Rubber support plate enables time-saving direct pick-up
- Optional flush-floor installation for easier passing over lift

DUETT lift unit:

- Lift with precise mechanical toothed rack synchronisation and simultaneous redundant mechanical safety feature
- Corrosion-proof hydraulic piston, self-lubricating since it dips into hydraulic oil with each stroke
- Low-noise operation due to very quiet motor in the installation

box

- Optionally usable with mineral organic oil with high durability
- Electronic lift control with visual error display
- Hydraulic power unit inside installation box (standard), can optionally be positioned outside
- Simple, suspended installation of the lift, ensuring advantageous force transmission into the hall floor
- High lifting/lowering speeds are guaranteed in a load-dependent range of 30 - 35 seconds
- Integrated, battery-operated emergency lowering
- Optimum workplace ergonomics thanks to optional, standard-independent control system via energy box or flush-mounted switching system

Scope of delivery:

- Flat head supports, hot-dip galvanised
- Medium-pressure lift unit with clamping system
- Wiring and mounting material
- Installation box/installation frame not included in delivery
- Emergency lowering cable for connection to switch box
- Control unit with 2 x 10 m control cable (oil flex cable)
- Lockable main switch
- Pinch point protection by CE stop instead of foot guard
- Operating instructions
- CE/UKCA Declaration of conformity

TECHNICAL DATA

Load capacity CE	3500 kg
Post distance	1350 mm
Longitudinal support extendable in notch steps	1400 - 2000 mm
Transverse support by repositioning	880 - 1820 mm
Size of support plate (L x B)	355 x 400 mm
Lifting height max.	1960 mm
Installation depth	2300 mm
Post diameter	90 mm

LIFTING TECHNOLOGY

TWO POST INGROUND LIFT

ZS DUETT 3.5 FT
VP 252319



TECHNICAL DATA

Toothed rack diameter, stainless steel	40 mm
Lifting/lowering time, load-dependent	approx. 35/35 s
Hydraulic oil quantity (not incl. in delivery) approx. 50 l	
Oil quality	HLP-D 22
Operating pressure	39 bar
Recommended installation box	VZ 972555
Control unit (H x W x D)	320 x 220 x 120 mm
Drive power	3.0 kW
Fuse protection gG	16 A
Power supply	3/N/PE 400 V 50 Hz

ACCESSORIES

VZ 972613 Reinforcement ZS DUETT 3.5 FT with post diameter 125 mm -EXTRA CHARGE-

VZ 972555 Installation tub for lifts 1350 mm cylinder distance MODEL: EW SA 1350

ACCESSORIES FOR FLAT LIFTING HEADS

VZ 972452 Flat lifting heads with extended support range 100 mm (1 set - 2 pcs) -EXTRA CHARGE-

VZ 972453 Flat lifting heads w. extra wide supports Model: R5G 3.5 -EXTRA CHARGE-

VZ 972423 Flat lifting heads with Granulate Coating instead of Rubber Support -EXTRA CHARGE-

VZ 975927 Rubber Chocks Set pyramidal h=40 mm, 120x120 mm (4 pcs.) MODEL: GK 12/4 set

VZ 975634 Rubber Chocks Set pyramidal h=80 mm, 120x120 mm (4 pcs.) MODEL: GK 12/8 set

VZ 975069 Plastic Chocks (4 pcs.) (47 x 132 x 340 mm)

VZ 975586 Rubber pads flat 100 x 150 x 20 mm (4 pieces)

FLUSH-FITTED INSTALLATION

VZ 972519 ZS Flat lifting head for flush-fitted installation

VZ 972420 Inst. Frame f. Flush Mounted 2 Post Inground Pad Type Lift Model: D-ER

SUPPLEMENTARY CHARGES

VT 998235 Transport Werkverkehr -SÜDEin-/Zwei-Stempel-Hebebühne mit Tragwerk

VT 998236 Transport Werkverkehr -NORDEin-/Zwei-Stempel-Hebebühne mit Tragwerk

VT 998237 Transport Werkverkehr -SÜDEinbauwanne (1 - 4 Stück)

VT 998238 Transport Werkverkehr -NORDEinbauwanne (1 - 4 Stück)

VT 998231 Transport Werkverkehr -SÜDEinfassungsrahmen

VT 998232 Transport Werkverkehr -NORDEinfassungsrahmen

VM 996001 Montagekosten ZweistempelHebebühne inkl. Tragwerk/Arme

VM 996007 Montagekosten EinstempelHebebühne inkl. Tragwerk/Arme

VM 996211 Montagekosten Einfassungsrahmen für bodenebene Flachträgerbrücke

VM 999035 Hydraulic Oil (HLP-D 22) per Litre -NET PRICE

VM 999036 Environmental-Friendly Hydr. Oil (PE-B 30), per litre -NET-

VV 997046 Packing Charges Post Inground Lift within Europe