

# PERFORMANCE MEASUREMENT TECHNOLOGY LUFTKÜHL- GEBLÄSE AIR

## AUXILIARY COMPONENT BLOWER VP 160009



## AUXILIARY COMPONENT BLOWER VP 160009

The moving auxiliary component blower is used for additional, targeted cooling of the intercooler, exhaust manifold, oil cooler and other areas of the vehicle. Because of its retractable and height-adjustable suspension, all sensitive vehicle areas can be easily reached and individually cooled.

### PRODUCT DETAILS/ACCESSORIES

Description:

- Extendible height-adjustable brackets for specific cooling of sensitive vehicle areas
- Additional targeted cooling of intercoolers, exhaust manifolds,

oil coolers and other areas

- Varnished with high-quality powder coating: Window Grey, RAL 7040

### TECHNICAL DATA

Volumetric flow	540 m <sup>3</sup> /h
Max. outflow speed at the nozzle	140 km/h
Motor power	2.2 kW
Fuse	16 A
Power supply	3/N/PE 400 V 50 Hz
Total weight	60 kg
Dimensions (H x W x L)	1150 x 470 x 1650 (max. 2650) mm
Max. projection	2000 mm

### ACCESSORIES

#### SUPPLEMENTARY CHARGES

VT 995055 Transportkosten Air 1, Air 2 und Bauteilzusatzgebläse