



technical data

VP 451196 / VP 451197		C_RGA 8.5 UC	
load capacity per column	8500 kg		
motor power per column	1,5 kW		
weight per column	525 kg		
full travel	1700 mm		
lifting height	1800 mm		
column width	180 mm		
frame width	1150 mm		
frame height	131 mm		
total height	2474 mm		
lifting time (load-dependent)	140 s		
lifting time - fast mode (load-dependent)	85 s		
Inner distance of support forks min. - max.	290 mm - 680 mm		
tyre diameter min. - max.	500 mm - 1500 mm		
fork length	380 mm		
lifting cycles at full load (without fast mode)	15		
lifting cycles at partial load (without fast mode, 3500 kg)	30		
safety class	IP 54		
noise emission	< 70 dB(A)		
hertzian stress on wheel (max.)	645 N/mm ²		
surface load floor plate (max.)	< 2 N/mm ²		
power supply	1x 100-240 VAC 50/60Hz; 2 A		
fuse	B 16A RCD (30 mA)		
energy supply	Lilon 50,4 VDC		

Schutzvermerk beachten nach DIN ISO 16016	Maßstab 1:15	Materialnummer 1409255	Revision 09	
	Konfigurationstyp	Dokumenttyp	Änderungsnr. 101594	Büro 300
		Benennung C_RGA 8.5 UC - Product Datasheet		
Datum, Ersteller 31.10.2023 KBRENNER		Datum, Prüfer 02.11.2023 NLASTOVK		Datum, Freigabe 02.11.2023 KBRENNER
Dokumentnummer F4901		Version I	Blatt A3	von
alte Materialnummer				